

# CONV-LAN-FIB-SM-SC

## SINGLE MODE FIBER TRANCEIVER



### FEATURES

- Single-mode Fast Ethernet Fiber Transceiver
- Power Cord and Manual Included
- Power: AC 100 -260V DC 1A@ + 5V
- Operating standards: IEEE 802.3u Fast Ethernet 10 /100 Base-TX and 100 Base-FX



### SPECIFICATIONS

Fiber Type	Single-mode
Operating Standards	IEEE 802.3u Fast Ethernet 10 /100 Base-TX and 100 Base-FX
<b>Connector</b>	
UTP	RJ-45 10/100/1000 Mbps
Fiber	SC 1000 Mbps
<b>Cable</b>	
UTP	Cat. 5 UTP (the max distance up to 100m)
Fiber: Single Mode	50/125, 62.5/125 m (the max distance up to 2km or 5km)
<b>Duplex Mode</b>	
Electrical Port	Full / Half Duplex
Optical Port	Full Duplex
LED	Power, FX FDX, FX Link/Act, TX 100, TX FDX, TX Link/Act.
Power	AC 100 -260V DC 1A@ + 5V
Ambient Temperature	0 – 70 °C
Humidity	5% - 90%
<b>Dimensions</b>	
Internal Power	30×110×140mm
External Power	26×70×93mm
*All product specifications and product images are subject to change without notice.	