


1. 5 wires analog resistive type touch panel
2. Easy for HDD installation
3. Fanless cooling system
4. IP65-rated front bezel

HPC104BR-FP7100




Features



- 10.4" 400 nits high brightness TFT LCD with LED backlight
- Intel® Kaby Lake i3-7100U 2.4GHz Dual Cores CPU
- 1* DDR4 SO-DIMM up to 16GB, 1* 2.5" SATA HDD (UPS Cell Option), 1* M.2 (M key, 2242)
- 4* USB3.0, 2* USB2.0 (Option), 2* RS232/422/485, 2* RS232 (Option), 2* Gigabit LAN
- 1* HDMI, 1* VGA (Option)
- Support wide voltage input 9-24V DC, with EOS, OVP design
- IP65-rated front bezel

Mechanical Dimension



*The Specification may be changed without further notice.
www.jetwayipc.com

Display

Front Bezel	IP65, NEMA 4 rugged protection, metal front bezel
Display Type	10.4" With LED Backlight
Brightness (cd/m²)	400 nits
Display Color	262K
Resolution	800 x 600 @60Hz
Viewing Angle (H/V)	130°/140°
Pixel Pitch	0.264 x 0.264mm
Aspect Ratio	4:3
Contrast Ratio	400:1
Response Time	25ms

Touch Screen

Type	5 wires analog resistive type
Active Range	246.03 x 191.42mm ±03mm
Transparency	80 ±3%
Surface Hardness	≥ 3H (pressure 750g/45°)
Operating Force	≤ 100g
Knock test	10,000,000 times keystrokes

Main System

CPU	Intel® Kaby Lake i3-7100U 2.4GHz/QC
RAM	DDR4 SO-DIMM up to 16GB
BIOS	128MB SPI Flash ROM
Storage	1* 2.5" SATA HDD (UPS Cell Option), 1* M.2 (M key, 2242)
Speaker	2* 3W/8Ω
Watchdog Timer	256 levels, 0~255 sec.
OS Support	Windows 10 / Linux

Power

Power Input	100~240V AC-DC 60W 9~24V DC with over current protection fuse
Consumption	35W

Dimensions

Case Dimensions	280.03 * 225.42 * 83.80mm
-----------------	---------------------------

Certifications

Certifications	CE, FCC, IP65 (Front)
----------------	-----------------------

I/O Connector

I/O Ports and Switches	4* USB3.0, 2* USB2.0 (Option), 1* Power button, 2* RS232 (Option), 2* RS232/422/485, 1* HDMI, 1* VGA (Option), 2* GbE, 1* Lockable Jack 9~24V DC-in
------------------------	---

Environment

Temperature	Operating: -10°C ~ +50°C Storage: -20°C ~ +70°C
Shock	/
Vibration	/

Expansion

Interface	1* M.2 (E key, 2230) for WIFI or 3G/4G
-----------	--



*The Specification may be changed without further notice.
www.jetwayipc.com