



I-7551

Isolated RS-232 to RS-232 Converter

Features

- 3000 VDC 3-way Isolation Protection
- Transmission Speed of up to 115200 bps
- Operating Temperatures, -25 °C ~ +75 °C
- ESD Protection
- Power Input, +10 ~ +30 VDC
- DIN-Rail Mounting



Introduction

The I-7551 provides a complete full-duplex (including control signal) electrical isolation channel between two RS-232 devices. This isolation is an important consideration if a system uses different power sources, has noisy signals, or must operate at different ground potentials.


The CTS/RTS pins of the I-7551 module can be reconfigured as DSR/DTR to meet requirements on different applications.

The I-7551 incorporates two DC-to-DC converters, the isolation side of the I-7551 is located in the input and output interface circuit. In other words, the I-7551 is 3-way isolated RS-232 to RS-232 converter.


System Specifications

Interface		
Input		TxD, RxD, CTS, RTS, GND (Default) or TxD, RxD, DSR, DTR, GND Jumpers JP1 and JP2 are used to select the RS-232 input source type
Output		TxD, RxD, CTS, RTS, GND (Default) or TxD, RxD, DSR, DTR, GND
Transmission Distance		Max. 15 M at 115200 bps
Speed		300 ~ 115200 bps
ESD Protection		Yes
3000 VDC Three Way Isolated Protection		Yes
Connector	RS-232 Input	9-Pin Female D-Sub
	RS-232 Output	9-Pin Male D-Sub
LED Indicators		
Power/Communication		Yes
Power		
Input Voltage Range		+10 VDC ~ +30 VDC (Non-isolated)
Power Consumption		1.2 W
Mechanical		
Casing		Plastic
Dimensions (W x H x D)		72 mm x 118 mm x 35 mm
Installation		DIN-Rail Mounting
Environment		
Operating Temperature		-25 °C ~ +75 °C
Storage Temperature		-30 °C ~ +75 °C
Humidity		10 ~ 90% RH, non-condensing

Applications



Pin Assignments




TxD, RxD, CTS, RTS, GND (Default)

RS-232 Input			RS-232 Output		
Pin Assignment	Terminal No.	Pin Assignment	Pin Assignment	Terminal No.	Pin Assignment
--	01	06 DTR	GND	05	09 --
TxD	02	07 CTS	--	04	08 CTS
RxD	03	08 RTS	TxD	03	07 RTS
DSR	04	09 --	RxD	02	06 --
GND	05		--	01	

Female DB-9 Connector

Male DB-9 Connector

Internal IO Structure




TxD, RxD, CTS, RTS, GND

RS-232 Input			RS-232 Output		
Pin Assignment	Terminal No.	Pin Assignment	Pin Assignment	Terminal No.	Pin Assignment
--	01	06 DTR	GND	05	09 --
TxD	02	07 CTS	DTR	04	08 --
RxD	03	08 RTS	TxD	03	07 --
DSR	04	09 --	RxD	02	06 DSR
GND	05		--	01	

Female DB-9 Connector

Male DB-9 Connector

Dimensions (Units: mm)



Ordering Information

I-7551 CR	Isolated RS-232 to RS-232 Converter (Blue Cover) (RoHS)
I-7551-G CR	Isolated RS-232 to RS-232 Converter (Gray Cover) (RoHS)

Accessories

GPSU06U-6	Power Supply, 110~240VAC or 127~230VDC to 24VDC/0.25A, 6 W, two pins USA plug
-----------	---