

PPC-IWRxx
Industrial Panel PC Series



Specifications

		PPC-IWR10	PPC-IWR12	PPC-IWR15	PPC-IWR17	PPC-IWR19
System	CPU	Supports Intel Celeron J1900 Processor Supports Intel Core i5 Processor				
	DDR	Supports 2GB 4GB 8GB DDR3 RAM (Not Included)				
	Storage	Supports 32GB 64GB 128GB 256GB 512GB SSD (Not Included) Supports 500GB 1TB HDD (Not Included)				
	Operation System	Support Windows OS				
	Touch screen	10-Point Projected Capacitive Touch				
Display	Screen	10.4" LCD Screen	12.1" LCD Screen	15" LCD Screen	17" LCD Screen	19" LCD Screen
	Resolution	1024 x 768 (4:3)	1024 x 768 (4:3)	1024 x 768 (4:3)	1280 x 1024 (4:3)	1366 x 768 (4:3)
	Front Bezel	5mm Ultra-thin Front Bezel with Rubber Seal Slot Rubber Seal (Optional) – Seals from dust and water				
	Color	16.7M				
	Contrast ratio	1000:1				
	Luminance	250 ~ 350 nits				
Network	WIFI	802.11b/g/n/ac				
	Ethernet	100M/1000M Ethernet				
Interface	Inputs	DC Input 4x USB 1x MIC 1x RJ45 1x HDMI Audio Input & Output				
Others	Wall mounting	VESA 75x75mm & 100 x 100mm				
	Panel Mounting	Panel mountable on all 4 sides of PPC				
	Speaker	2 x 3W				
	Language	Multi-language				
	Working temperature Storage Temperature	0°C~50°C -20°C -- 60 °C				
	Power	12V 5A				
	Materials	Metal Case, Black				

*All product specifications and product images are subject to change without notice.

www.cme.co.za

Specifications (Wide Screen Options)

		PPC-IWR156	PPC-IWR215
System	CPU	Supports Intel Celeron J1900 Processor Supports Intel Core I5 Processor	
	DDR	Supports 2GB 4GB 8GB DDR3 RAM (Not Included)	
	Storage	Supports 32GB 64GB 128GB 256GB 512GB SSD (Not Included) Supports 500GB 1TB HDD (Not Included)	
	Operation System	Support Windows OS	
	Touch screen	10-Point Projected Capacitive Touch	
Display	Screen	15.6" (16:9) 1366 x 768	21.5" (16:9) 1920 x 1080
	Front Bezel	5mm Ultra-thin Front Bezel with Rubber Seal Slot Rubber Seal (Optional) – Seals from dust and water	
	Color	16.7M	
	Contrast ratio	1000:1	
	Luminance	250 ~ 350 nits	
Network	WIFI	802.11b/g/n/ac	
	Ethernet	100M/1000M Ethernet	
Interface	Inputs	DC Input 4x USB 1x MIC 1x RJ45 1x HDMI Audio Input & Output	
Others	Wall mounting	VESA 75x75mm & 100 x 100mm	
	Panel mounting	Panel mountable on all 4 sides of PPC	
	Speaker	2 x 3W	
	Language	Multi-language	
	Working temperature Storage Temperature	0°C~50°C -20°C -- 60 °C	
	Power	12V 5A	
	Materials	Metal Case, Black	

*All product specifications and product images are subject to change without notice.

Ordering Information

Screen Size	J1900 CPU P-CAP Touch 0G RAM 0G SSD	Core I5 CPU P-CAP Touch 0G RAM 0G SSD
10.4" 12" 15" 17" 19"	PPC-IWR10-J19 PPC-IWR12-J19 PPC-IWR15-J19 PPC-IWR17-J19 PPC-IWR19-J19	PPC-IWR10-I5 PPC-IWR12-I5 PPC-IWR15-I5 PPC-IWR17-I5 PPC-IWR19-I5
15.6" 21.5"	PPC-IWR156-J19 PPC-IWR215-J19	PPC-IWR156-I5 PPC-IWR215-I5

