

SHIELD-D-4L-NT-N100

Micro Firewall Appliance



Features

- Onboard Intel® Alder lake-N N100 Processor
- Support DDR4 RAM, Max. 32GB
- Support M.2 PCIe Port
- Support HDMI 2.0 & DP 1.4
- Support 6x USB
- Support OS: Windows 10/11 & Linux

Accessories

Power Supply | HDMI Cable | VESA Mount



Specifications

CPU	Intel® Alder lake-N N100 (4C/4T, max 3.4GHz) TDP 6W Processor	
GPU	Intel® UHD Graphics	
Memory	1 x SODIMM DDR4 2666/2933/3200 (Max 32GB)	
Storage	1 x M.2 2280 SATA SSD 1 x 2.5" inch SATA SSD/HDD	
Wireless	m.2 PCIe Port	
Display Port	HDMI 2.0 + DP1.4	
Front Panel	Power Button 1x USB 3.0 Type-C 1x USB 3.0	4x USB 2.0 1x SIM Card (4G/5G) HDMI + DP
Back Panel	3x 2.5G LAN Port (LAN1-LAN3), Intel I225 1x 2.5G LAN Port (LAN4) Support POE IN 1x COM232/485/422 1x DC IN	
Port on the MB	1x SATAIII 1x M.2 Slot for 4G/5G Module 1x USB 2.0 Header 1x COM Header: 2x COM	
Power	Input: 100 – 240V AC Output: 12V3A DC	
VESA	Support 70 x 70 100 x 100mm	
BIOS	Wake On Lan UEFI Auto power on when power failure PXE	
Dimensions	155 x 126.5 x 62mm	
Chassis	Metal	
OS Support	Windows 10 11 & Linux	

** All product specifications and product images are subject to change without notice.

www.cme.co.za