

Q5

2U Active Air Cooler

PRODUCT SPECIFICATIONS

Q5| Socket LGA 1700**Model Number: Q5**

- Recommend for Intel® CPU as following
 - Support Intel Core 12th -15th Gen, Socket LGA1700/1851
- Active Cooler for 2U Server & Up

Overall Specification


Dimension	90.7 x 85.0 x 65.1 mm
Weight	515±5g
Material	Copper Base & Aluminum Fins with Heat Pipe embedded
Fan	6025 Side-blow fan with PWM Function
Mounting Method	Cooler Mounted in Captive design
Back Strip Set	Included
Thermal Grease	SHIN-ETSU 7762 or Equivalent
TDP	Up to 185 Watts at 30° ambient temperature

Cooling Fan Specification

Dimension	60 x 60 x 25 mm
Bearing	Double Ball
Rated Voltage	12V
Rated Speed	At Duty Cycle 0~20%: 1600± 200 RPM At Duty Cycle 50%: 4000± 10% RPM At Duty Cycle 100%: 8000 RPM
Input Power	At Duty Cycle 0~20%: 1.20 W At Duty Cycle 50%: 2.28 W At Duty Cycle 100%: 7.20 W
Maximum Airflow	At Duty Cycle 0~20%: 9.28 CFM At Duty Cycle 50%: 23.21 CFM At Duty Cycle 100%: 46.41 CFM
Rated Static Pressure	At Duty Cycle 0~20%: 0.76 mm-H2O At Duty Cycle 50%: 4.76 mm-H2O At Duty Cycle 100%: 19.04 mm-H2O
Acoustical Noise	At Duty Cycle 0~20%: 18 dBA At Duty Cycle 50%: 37.89 dBA At Duty Cycle 100%: 52.94 dBA
Lead Wire Pin Out	Pin#1- Black(-) Pin#2- Yellow(+) Pin#3- Green(Tachometer/ Signal Output) Pin#4- Blue (PWM)

Performance Chart: Active Cooler Q5 Thermal Resistance



Thermal Resistance vs. Fan Speed (Duty Cycle and RPM)



CONFIDENTIAL DOCUMENT

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO DYNATRON CORPORATION AND DYNATRON INDUSTRIAL CO., LTD. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DRAWING IS EXPRESSLY PROHIBITED EXCEPT AS DYNATRON CORPORATION AND DYNATRON INDUSTRIAL CO., LTD. MAY OTHERWISE AGREE TO IN WRITING.

REV#	DESCRIPTION	CHECKER	DATE
0.0	INITIAL RELEASE	JOY	02/24/21
1.0	FAN UPDATE	JOY	06/29/21
2.0	BACKPLATE UPDATE	JOY	10/07/21
3.0	ADD WASHER	JOY	11/08/21






15	FAN, DF126025BH-8000RPM	PLASTIC	1
14	FAN MOUNTING SCREW	STEEL	4
13	BACKPLATE	SPCC	1
12	INSULATOR	FORMEX GK-17	1
11	ADHESIVE TAPE	3M	1
10	THERMAL GREASE	SHIN-ETSU 7762	1
9	BRACKET SCREW	STEEL	4
8	COVER MOUNTING SCREW	STEEL	4
7	C-RING	STEEL	4
6	BRACKET	SK-7	2
5	HEATSINK	COPPER BASE+AL FIN + HEATPIPE x3	4
4	SPRING	SUS 304	1
3	WASHER	STEEL	4
2	SCREW, HEATSINK	STEEL	4
1	FAN COVER	ALUMINUM	1
ITEM #	DESCRIPTION	MATERIAL	QTY.

NOTES:
1. OVERALL DIMENSION: 90.7x85.0x65.1 mm
2. THE FIGURE IS FOR REFERENCE ONLY, AND NOT FOR SCALE

	DATE	NAME	 DYNATRON CORPORATION
DRAWN	02/24/21	enr.	TITLE:
CHECKED	06/29/21	enr.	2U Active Cooler Q5
ENG. APPR.			BDM & Exploded Assembly Drawing
MFG. APPR.			
QA			
COMMENTS:			
		DWG. No:	REV
		DYN-EP-Q5	3.0

REV#	DESCRIPTION	CHECKER	DATE
0.0	INITIAL RELEASE	JDY	02/24/21
1.0	BACKPLATE UPDATE	JDY	10/07/21
2.0	ADD VASHER	JDY	11/09/21



	NAME	DATE
DRAWN BY	ENGR	02/24/2021
CHECKED BY	ENGR	02/24/2021
ENG.APPROVED		
MFG.APPROVED	-	-



DYNATRON CORPORATION

TITLE: 2U ACTIVE COOLER
Q5
Overall Dimension Drawing

CONFIDENTIAL DOCUMENT
THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO DYNATRON CORPORATION AND DYNAEON INDUSTRIAL CO., LTD. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DRAWING IS EXPRESSLY PROHIBITED EXCEPT AS DYNATRON CORPORATION AND DYNAEON INDUSTRIAL CO., LTD. MAY OTHERWISE AGREE TO IN WRITING.

VIEW	
UNITS	MM

DWG. No: DYN-BD-Q5

REV. 2.0