SONOFF Zigbee Motion Sensor | SNZB-03P

Illuminate Your Path, Secure Your Space




















Motion Detection

Trigger to turn on smart lights to welcome you home







Automate your staircase lighting




+



SNZB-03P

Smart Switch



Senseless trigger night lights




+



SNZB-03P

Smart RGB strip light


Combining Convenience And Energy Conservation



Smart Environment Light Detection


When detecting movement, intelligently determine whether the ambient brightness is dim or bright, allowing you to have more flexibility in deciding whether to turn on the lights.





Extended Battery Life

Using CR2477 battery extends the battery life to over 3 years, eliminating concerns about frequent battery replacements.



*The battery life is a theoretical value obtained through internal laboratory testing by SONOFF, with a test environment of 25°C, connected to the SONOFF gateway, and triggered 50 times a day. Actual battery life may vary depending on usage.

Home Security



Receive App notifications when movement is detected, no matter where you are.




Trigger NSPanel Pro to make an alarm.



Trigger cam s lim to record a video and save it in an SD card or cloud.

Local Scene Intelligent Linkage

Even if your WiFi network crashes, you can still activate Zigbee local scenes as long as your Zigbee devices are powered on. Lower latency, higher reliability.





Explore More Possibilities

Based on eWeLink App Third-party platform function, supporting Alexa, Google Home, Smartthings, Alice and IFTTT.















*To access the eWeLink App, SONOFF ZBBridge-P/NSPanel Pro/iHost is needed. The IFTTT function requires eWeLink Advanced Plan.

Compatible with Multiple Zigbee Hubs




Add to Home Assistant

Easily add to Home Assistant for your home automation through ZHA or Zigbee2MQTT



*To access the HA, Dongle is needed(e.g. SONOFF ZBDongle-P, ZBDongle-E).
The user interface (UI) enhancement of Zigbee2MQTT is scheduled to be launched in January 2024.

Place Anywhere and Cover Anywhere





Battery-powered, no wires needed. Features a magnetic suction design, allowing it to stick anywhere and rotate to any angle.



^{*3}M adhesive tape and screws are available as options

Various Installation Methods







Difference between Presence Sensor and Motion Sensor

	Presence Sensor (SNZB-06P)	Motion Sensor (SNZB-03P)		
Zigbee Device Type	Router	End device		
Principle	Using microwave radar to detect moving objects	Using a pyroelectric infrared sensor to detect changes in infrared radiation		
Minimum Detection Duration (Timeout)	15s	5s		
Detection Distance	Up to 4m(13ft)	6m(20ft)		
Motion Detection	✓			
Stationary Person Detection	✓	N/A		
Power Supply	Powered by Type-C 5V 1A cable	Powered by CR2477 battery, no wires needed, more flexibile to install		
Suitable Scenes				
	Bathrooms, office desks, reading, and other scenarios that require continuous detection of stationary people	Entrances, corridors, stairs, and other scenarios where people only briefly stop and may not have power sockets		
Additional Information	Other moving objects like pets, curtains, Roombas, and running fans also will be detected. Please avoid being near these objects	Prone to temperature interference, please avoid being near heat sources. Objects with temperatures similar to the human body, such as pets, may be detected		

In the Box



Feature Overview

		15:30				
	ZBBridge-P	NSPanel Pro	iHost	ZBBridge	Zigbee2MQTT	Other Platforms
Motion Detection	/	✓	/	/	/	~
History Record	~	~	~	~	~	Not Guaranteed
Custom Detection Duration	/	/	~	×	/	×
Ambient Brightness (Bright/Dim)	/	~	~	×	/	×
Local Scene	/	/	/	×	/	Not Guaranteed

Specification

Model

SNZB-03P

Wireless connection

Zigbee 3.0

Detection range

6m(20ft), 110°

Battery model

CR2477(3V)

Casing material

PC

Working temperature

-10°C ~ 60°C

Working humidity

5-95%RH, non-condensing



Product dimension

44x44x65mm

Net weight

54g