



2025-2026 IPC Products

Taiwan Headquarter

Jetway Information Co., Ltd.
9F, No.207, Sec. 3, Beixin Rd., Xindian Dist.,
New Taipei City, 23143, Taiwan
Tel : +886-2-89132711
e-mail: support_team@jetway.com.tw
www.jetwayipc.com

USA

Jetway Computer Corp.
8058 Central Ave, Newark, CA 94560. USA.
Tel: +1-510-857-0130
e-mail: sales@jetwaycomputer.com



Z-A131-F

WHO IS JETWAY?

Jetway has designed and manufactured industrial Class Embedded Motherboards, Barebones, Rackmounts, Panel PC and other electronic products for over 30 years. All products are designed to meet international standards and manufactured under the ISO quality system. Our research and development team is well versed in a broad range of the latest technology and able to deliver short turn-around time products and applications to meet current market requirements.

Jetway follows the Intel Embedded Roadmap for processors and chipsets, enabling our products to have up to 15 years of planned lifecycle. Lower TCO, spend less time redesigning your products and save time and money supporting your products over your products lifecycle. Jetway has a wide selection of off the shelf motherboards and barebones, as well as OEM or ODM services, offering customized solutions for your exact requirements.

Jetway providing:

Local Sales

Local Support

Local Inventory

Long Planned Lifecycle

Motherboard Form Factors:

Pico-ITX	3.9" x 2.8"
NUC	3.9" x 3.9"
EPIC	6.4" x 4.5"
3.5" SBC	5.8" x 4.0"
Mini-ITX	6.69" x 6.69"
Micro ATX	9.6" x 9.6"
ATX	12.0" x 8.6"
Proprietary	varies

Markets & Applications

Digital Signage

Kiosk

IoT/Edge/AI

Network Appliance

Industrial Automation

Fanless Computer

Embedded Systems

Casino Gaming

Surveillance/Security

Manufacturing Systems

Robotics

Point of Sale/Retail

And more...



Support



Solution



Service



Contact



JPIC-ADN1



PICO

Intel® Processor N97
1 x DDR5 4800MHz SO-DIMM up to 32GB
1 x Realtek RTL8111H GbE
EXT : 2 x USB 3.2 (Gen.2)
INT : 4 x USB 2.0
1 x HDMI / 1 x LVDS (option eDP)
INT : 2 x RS-232/RS422/485
12V DC-in

PIC-ASL1



PICO

Intel Atom® x7433RE/x7213RE Processor
1 x DDR5 4800MHz SO-DIMM up to 32GB
1 x Realtek RTL8111H GbE
EXT : 2 x EXT USB 3.2 (Gen.2)
INT : 4 x USB 2.0
1 x HDMI / 1 x LVDS (option eDP)
INT : 2 x RS-232/RS422/485
12V DC-in

MF30



3.5"

Intel Raptor Lake i5-1335UE/ i5-1335U
SoC Processor
2 x DDR5 4800MHz SO-DIMM up to 64GB
1 x Intel i226-LM 2.5GbE, 1 x Intel i226-V 2.5GbE
EXT: 3 x USB 3.2 (Gen.2)
EXT: 1 x USB 3.2 (Gen.2) Type-C support
DP ALT Mode, 4 x INT USB 2.0
2 x HDMI / 2 x DP / 1 x USB3.2 Type-C /
1 x LVDS(eDP)
INT : 4 x RS-232/422/485, 2 x RS-232
12V DC-in

MF32



3.5"

Intel® Raptor Lake i5-1335UE/ U300
SoC Processor
1 x DDR5 4800MHz SO-DIMM up to 32GB
1 x Intel i226-LM 2.5GbE
3 x Intel i226-V 2.5GbE
EXT : 2 x USB 3.2 (Gen.2)
INT : 4 x USB2.0
1 x HDMI
EXT : 1 x RS-232 (RJ50 Type)
INT : 1 x RS-232/422/485
19V DC-in

F35-MTU1



3.5"

Intel® Core™ Ultra 125U/ 155U SoC
Processor
2 x DDR5 5600MHz SO-DIMM up to 96GB
1 x Intel i226-LM 2.5GbE
1x Intel i226-V 2.5GbE
EXT: 3 x USB 3.2 (Gen.2)
EXT: 1 x USB 3.2 (Gen.2) Type-C
INT : 4 x USB2.0
2x HDMI / 1x LVDS(eDP) / 1x DP / 1x Type C DP
INT: 2x RS-232/422/485, 2x RS-232
12~36V DC-in

MF04E



3.5"

Intel® J6412 SoC Processor
2 x DDR4 3200MHz, Dual Channel
SO-DIMM up to 32GB
2 x Intel i226-V 2.5GbE
EXT: 3 x USB 3.1
EXT: 2 x USB 2.0
INT : 2 x USB 2.0
2* HDMI / 1 x eDP(LVDS)
INT : 1 x RS-232/422/485
INT : 1 x RS-232
12~24V DC-in

F35-ASL1



3.5"

Intel Atom® x7433RE Processor
1 x DDR5 4800MHz, Single Channel
SO-DIMM, up to 32GB
2 x Intel i226-V 2.5GbE
EXT: 1 x USB 3.2
EXT: 1 x USB 3.2 (Gen.2) Type-C support
DP ALT Mode, 4 x USB 2.0
INT : 4 x USB2.0
1 x HDMI / 1 x LVDS(eDP) / 1 x Type C DP
INT : 1 x RS-232/422/485, 5 x RS-232
12~28V DC-in

JNUC-ADN1



NUC

Intel® Processor N97
1 x DDR5 4800MHz, Single Channel
SO-DIMM, up to 32GB
2 x Intel i226-V 2.5GbE
EXT: 2 x USB 3.2
EXT: 2 x USB 3.2 (Gen.2) Type-C support
DP ALT Mode, 1 x USB 2.0
INT : 2 x USB2.0
1 x HDMI / 2 x Type C DP / 1 x DP
INT : 1 x RS-232/422/485
12~19V DC-in

MTX-MTH1



Mini-ITX

Intel Meteor Lake 155H/125H SoC Processor
2 x DDR5 5600MHz SO-DIMM, up to 96GB
Realtek Audio Codec
1 x Intel I226-LM 2.5GbE, 2 x Intel I226-V 2.5GbE
EXT : 2 x USB 3.2 Gen 2, 2 x USB 2.0
INT : 2 x USB 3.2, 2 x USB 2.0
4 x HDMI 2.1/1 x LVDS(eDP)
INT : 2 x RS-232/422/485, 4 x RS-232
1 x M-Key 2242, 1 x M-Key 2242/2280
1 x B-Key 3042/3052, 1 x E-Key 2230
1 x PCIe Gen.5x8, DC-in 12~36V

MTX-ARH1



Mini-ITX

Intel Arrow Lake-H 255H/225H SoC Processor
2 x DDR5 5600MHz SO-DIMM, up to 96GB
Realtek Audio Codec
1x Intel I226-LM 2.5GbE, 2 x Intel I226-V 2.5GbE
EXT : 2 x USB 3.2 Gen 2, 2 x USB 2.0
INT : 2 x USB 3.2, 4 x USB 2.0
4 x HDMI 2.1/1 x LVDS(eDP)
INT : 2 x RS-232/422/485, 4 x RS-232
1 x M-Key 2242, 1 x M-Key 2242/2280
1 x B-Key 3042/3052, 1 x E-Key 2230
1 x PCIe Gen.5x8, DC-in 12~36V

UTX-ARS1

Coming Soon

Micro-ATX

Intel LGA 1851 Socket Processor Intel Q870 chipset
4 x DDR5 5600MHz U-DIMM, up to 192GB
Realtek Audio Codec
EXT: 6 x USB 3.2 Gen 2
INT : 2 x USB 3.2 Gen 1, 6 x USB 2.0
2 x HDMI 2.1/1 x LVDS(eDP)
EXT: 1 x RS-232/422/485, INT : 5 x RS-232
1 x M-Key 2242/2260/2280/22110
1 x B-key 3042/3052, 1 x E-Key 2230
1x PCIe Gen.5 x16, 2x PCIe Gen.4 x4, 1x PCIe Gen.4 x1
ATX Power Supply

MTX-ASL1



Mini-ITX

Intel Amoston Lake x7211RE/x7433RE SoC Processor
1 x DDR5 4800MHz SO-DIMM, up to 32GB
Realtek Audio Codec
EXT : 1 x USB 3.2 Gen 2, 1 x USB 3.2 Gen 2 Type-C
Support DP ALT Mode, 2* USB 2.0
INT : 4 x USB 2.0
2x HDMI 2.0b/1x LVDS (eDP)/1x Type C DP1.4
EXT : 1 x RS-232/422/485
INT : 5x RS-232
1xM-Key 2242/2280, 1xB-Key 3042/3052, 1xE-Key 2230
DC-in 12~28V

LI39-64120



Mini-ITX

Intel Elkhart Lake J6412 SoC
Processor
1 x DDR4 3200MHz SO-DIMM up to 32GB
2 x Intel i226-V 2.5GbE
EXT: 4 x USB3.2 (Gen1)
INT: 5 x USB 2.0
HDMI/LVDS/EDP
EXT: 1 x RS232
INT: 3 x RS232, 2 x INT RS485
12V DC-in

DMTX-ADN1-N9700



Mini-ITX

Intel Alder Lake-N N97 SoC Processor
1 x DDR5 4800MHz SO-DIMM up to 32GB
2 x Realtek RTL8111H GbE
EXT: 2 x USB3.2 (Gen1), 2 x USB2.0
INT: 6 x USB 2.0
HDMI / DP / LVDS or EDP/EDP
(COM1/2 support 5V/12V Selectable)
INT: 4 x RS232
(COM1/2 support 5V/12V Selectable)
12V DC-in


JLI1U-20



Mini-ITX

AMD™ RYZEN™ V1605B Core
Processor
2 x DDR4 2400 SO-DIMM up to 32GB
2 x Realtek® GbE
Rear: 2 x USB3.2 (Gen1), 2 x USB2.0
INT: 6 x USB 2.0
4 x DP1.4, 1 x eDP, 1 x LVDS
Rear: 2 x RS232/422/485
INT: 4 x RS232
12~28V DC-in


LM26-H6100



Micro ATX

Intel 12/13th LGA 1700 Socket
Processor
2 x DDR4 3200 U-DIMM up to 64GB
1 x Intel GbE, 2 x Intel 2.5GbE
EXT: 3 x USB3.2 (Gen1), 3 x USB2.0
INT: 4 x USB2.0, 1 x USB2.0 (Vertical Type-A)
HDMI/DP/VGA
EXT: 2 x RS232/422/485
INT: 8 x RS232
24pin ATX + 8pin 12V


LA34-H6100



ATX

Intel 12/13th LGA 1700 Socket
Processor
2 x DDR5 4800 U-DIMM up to 64GB
1 x Intel GbE, 3 x Intel 2.5GbE
EXT: 4 x USB3.2 (Gen1), 2 x USB2.0
INT: 4 x USB2.0, 2 x USB2.0 (Vertical)
HDMI/DP/VGA/LVDS or eDP
EXT: 2 x RS232/422/485
INT: 4 x RS232 (COM3~4: 5V/12V)
24pin ATX + 8pin 12V


LA2H-H420E



ATX

Intel 10/11th LGA 1200 Socket
Processor
2 x DDR4 LONG DIMM 2933/2666
DRAM up to 64GB
1 x Intel 2.5GbE, 1 x Intel GbE
Rear: 4 x USB3.2 (Gen1), 2 x USB2.0
INT: 2 x USB2.0, 1 x USB 2.0 (Vertical)
2 x HDMI, 1 x VGA
Rear: 2 x RS232/422/485
INT: 4 x RS232
24pin ATX + 8pin 12V

NAF791-Q370



ATX

Intel 8th LGA 1151 Socket
Processor
4 x DDR4 2666 U-DIMM up to 128GB
2 x Intel GbE
EXT: 4 x USB3.1 (Gen2), 2 x USB3.1 (Gen1)
INT: 2 x USB3.1 (Gen1), 4 x USB2.0
HDMI/DP/VGA/DVI-D
EXT: 1 x RS232/422/485
INT: 8 x RS232, 1 x RS232/422/485
24pin ATX + 8pin 12V

HB652I3H-R680-AI4



Edge AI Performance

306(W) x 199(D) x 79(H) mm
Intel 13th LGA1700 Socket Core Processor, Intel R680E chipset
2 x DDR5 5600 SO-DIMM up to 64GB
2 x Intel 2.5GbE
8 x USB3.2 (Gen2), 2 x USB2.0
1 x HDMI
2 x RS232/422/485, 4 x RS232
12~36V DC-in

HB190MA3H-R680-AI4



4U Rack Edge AI Server

480(W) x 430(D) x 177(H) mm
Intel 13th LGA1700 Socket Core Processor, Intel R680E chipset
4 x DDR5 4800 Long-DIMM up to 128GB support ECC
2 x Intel 2.5GbE
8 x USB3.2 (Gen2), 2 x USB2.0
1 x HDMI2.0b
1 x RS232/422/485, 1 x RS232
ATX 24pin + 8pin Power in
ATX 500W

HB368F21-6412-AI



Edge AI Performance

160.2(W) x 106(D) x 43.5(H) mm
Intel® Celeron® Processor J6412
1 x DDR4 3200 SO-DIMM up to 32GB
2 x Realtek GbE
2 x USB3.1 (Gen2), 5 x USB2.0
3 x DP
2 x RS232/422/485 (2*9 PIN)
12~36V DC-in

HM-5002



Robust Din-rail Fanless System

216.8(W) x 124(D) x 86(H) mm
Intel® Core™ i5-8365UE Processor
2 x DDR4 2400/2133SO-DIMM up to 64GB
2 x Intel GbE, 4 x PoE GbE (I350AM4)
2 x USB3.0, 2 x USB2.0
1 x HDMI1.4b, 1 x DP1.2
2 x RS-232/422/485 (DB9 type)
12~36V DC-in

HBJC903I39-6412-N



Edge AI Performance

200.0(W) x 180.4(D) x 59.5(H) mm
Intel Elkhart Lake SoC Processor
1 x DDR4 3200 SO-DIMM up to 32GB
2 x Intel i226-V 2.5GbE
2 x USB3.2 (Gen.1), 4 x USB 2.0
1 x HDMI2.0
4 x RS-232 or 2 x RS-232 + 2 x RS-485 (DB9 type)
12V DC-in

N11-1115



Compact

121(W) x 113.4(D) x 59(H) mm
Intel® Core™ i3-1115G4 Processor
2 x DDR4 3200 SO-DIMM up to 64GB
1 x Intel GbE, 1 x Intel 2.5GbE
2 x USB3.2 (Gen2), 3 x USB3.2 (Gen2) Type-C
2 x HDMI, 2 x DP (From USB Type-C)
12~24V DC-in

HBJC330U10-45G7-B



Compact

16(W) x 110(D) x 49(H) mm
Intel® Celeron® Processor
1 x DDR3L 1866 SO-DIMM up to 8GB
2 x Realtek GbE
4 x USB3.0
2 x HDMI, 1 x VGA
1 x RS232/422/485
12V DC-in

HBJC313U691-345B



Compact

116(W) x 110(D) x 49(H) mm
Intel® Celeron® Processor
1 x DDR3L 1866 SO-DIMM up to 8GB
2 x Realtek GbE
4 x USB3.0
2 x HDMI, 1 x VGA
1 x RS232/422/485
12V DC-in

HBJC420U11-4125B



Compact

129(W) x 109.4(D) x 34(H) mm
Intel® Celeron® Processor J4125
1 x DDR4 2400 SO-DIMM up to 8GB
2 x Realtek GbE
3 x USB3.1, 1 x USB3.1 Type-C
2 x HDMI / 1 x DP
1 x RS232/422/485, 1 x RS232
12V DC-in

HBFBU03-6412-B



Compact

125(W) x 109.2(D) x 44.5(H) mm
Intel® Celeron® Processor J6412
1 x DDR4 3200 SO-DIMM up to 16GB
2 x Intel 2.5GbE
2 x USB3.1 (Gen2), 2 x USB3.1 (Gen2) Type-C, 1 x USB2.0
2 x HDMI / 1 x DP
12V DC-in

BFBLZ39-64120-N



Compact

180(W) x 89(D) x 50(H) mm
Intel Elkhart Lake J6412 Processor
1 x DDR4 3200 SO-DIMM up to 32GB
2 x Intel i226-V 2.5GbE
4 x USB3.2 (Gen.1)
1 x HDMI
2 x RS232/422/485
12V DC-in

HBFBZ10-6412-B



Compact

125(W) x 109(D) x 39.5(H) mm
Intel® Celeron® Processor J6412
1 x DDR4 3200 SO-DIMM up to 16GB
4 x Intel 2.5GbE
1 x USB3.1 (Gen2), 1 x USB2.0
HDMI
1 x RS232 (RJ-45 Type)
12V DC-in

BFBLZ38



Compact

161.0(W) x 89.0(D) x 67.0(H) mm
Intel® Celeron® Processor J Series
1 x DDR4 3200MHz SO-DIMM up to
32GB
7 x Intel 2.5GbE
2 x USB3.2 (Gen1)
1 x HDMI
1 x Console (RS232/422/485)
12V DC-in

HBFBP01-6210-B



Comapct

125(W) x 109(D) x 44.5(H) mm
Intel® Celeron® Processor N6210
1 x DDR4 3200 SO-DIMM up to 16GB
2 x Realtek GbE
2 x USB3.1 (Gen2), 1x USB3.1
(Gen2) Type-C
HDMI
1 x RS232/422/485
9~36V DC- in

HB650I02-Q470-B/T



Performance

224(W) x 199(D) x 63(H) mm
Intel 10/11th LGA 1200 Socket
Processor, Intel Q470E chipset
2 x DDR4 2933/2666/2499
SO-DIMM up to 64GB
1 x Intel GbE, 1 x Intel 2.5GbE
4 x USB3.2 (Gen1), 4 x USB2.0
2 x HDMI, 1 x DP
Option: 2 x RS232/422/485, 2 x COM
12~28V DC-inr

HBFFI02-Q470-B



Performance

290(W) x 207(D) x 65(H) mm
Intel 10/11th LGA 1200 Socket
Processor, Intel Q470E chipset
2 x DDR4 2933/2666/2400
SO-DIMM up to 64GB
1 x Intel GbE, 1 x Intel 2.5GbE
4 x USB3.2 (Gen2), 2 x USB2.0
2 x HDMI / 1 x DP
2 x RS232/422/485, 2 x RS232
12~28V DC-in

HBJC511I09-H470-B



Performance

264(W) x 199.4(D) x 38(H) mm
Intel 10/11th LGA 1200 Socket
Processor, Intel H470 chipset
2 x DDR4 2933/2666/2400 SO-DIMM
up to 64GB
1 x Intel GbE
3 x USB3.2 (Gen2), 1 x USB3.2 (Gen1)
Type-C, 4 x USB2.0, 1 x HDMI, 1 x DP
1 x RS232/422/485
12~19V DC-in

HBFFF797-Q37-V



Performance

290(W) x 207.4(D) x 65(H) mm
Intel® Celeron® Processor J6412
1 x DDR4 3200 SO-DIMM up to 32GB
6 x Intel 2.5GbE(4 x PoE LAN)
2 x USB3.2 (Gen1)
1 x HDMI
1 x RS232/422/485, 3 x RS232
12V DC-in
PoE LAN: 9~36V DC Power in

HBJC903MTX-9700-N



HBJC903MTX-9700-N



Performance

290(W) x 207.4(D) x 65(H) mm
Intel® Celeron® Processor J6412
1 x DDR4 3200 SO-DIMM up to 32GB
6 x Intel 2.5GbE(4 x PoE LAN)
2 x USB3.2 (Gen1)
1 x HDMI
1 x RS232/422/485, 3 x RS232
12V DC-in
PoE LAN: 9~36V DC Power in

Edge AI Performance

200.0(W) x 180.4(D) x 59.5(H) mm
Intel Alder Lake-N N97 SoC Processor
2 x DDR4 4800 SO-DIMM up to 32GB
2 x Realtek RTL8111H GbE
2 x USB3.2 (Gen1), 8 x USB2.0(FP)
1 x HDMI / 1 x DP
2 x RS232/485, 2 x RS232
12V DC-in

B420PADN1



Compact

129(W) x 109.4(D) x 34(H) mm
Intel® Aldar Lake N97 Processor
1 x DDR5 4800MHz, Single Channel SO-DIMM, up to 32GB
1 x RJ45 for Realtek® RTL8111H GbE
2 x USB 3.2 (Gen2)
2 x USB 2.0
1 x HDMI 2.0b
2 x RS232/422/485
12V DC-in

B382FRPU1



Performance

185(W) x 142(D) x 61(H) mm
Intel® Raptor Lake i5-1335U SoC Processor
2 x DDR5 4800MHz, Dual Channel SO-DIMM, up to 64GB
1 x RJ45 for Intel® i226-V 2.5GbE
1 x RJ45 for Intel® i226-LM 2.5GbE
3 x USB 3.2 (Gen2), 4 x USB 2.0, 1 x USB Type-C
2 x HDMI 2.0b
2 x 2 x DP1.4
4 x RS-232/422/485
19V DC-in

BFLFRPU2



Compact

160.0 (W) x 142 (D) x 52 (H) mm
Intel® Raptor Lake i5-1335UE/ U300 SoC Processor
1 x DDR5 4800MHZ SO-DIMM up to 32GB
1 x RJ45 for Intel i226-LM 2.5GbE
3 x RJ45 for Intel i226-V 2.5GbE
2 x USB3.2 (Gen2)
1 x HDMI 1.2
1 x RS-232 (RJ50 Type)
1 x RS-232/422/48
19V DC-in

BFTFASL1



Performance

160.0 (W) x 109.2 (D) x 50.5 (H) mm
Intel Atom® x7433RE Processor
1 x DDR5 4800MHz, Single Channel SO-DIMM, up to 32GB
2 x RJ45 for Intel® i226-V 2.5GbE
1 x USB 3.2 Gen 2 Type-C
1 x USB 3.2 Gen 2 Type-A
4 x USB 2.0
2 x HDMI 2.0b/ 1 x Type C DP1.4a
1 x RS-232/422/485, 1 x RS-232
12V DC-in

B382FMTU1



Performance

185(W) x 142(D) x 61(H) mm
Intel® Core™ Ultra 125U/ 155U SoC Processor
2 x DDR5 5600MHz SO-DIMM up to 96GB
1 x RJ45 for Intel i226-LM 2.5GbE
1 x RJ45 for Intel i226-V 2.5GbE
3 x USB3.2 (Gen2)
1 x USB3.2 (Gen2) Type-C
4 x USB2.0
2 x HDMI 2.0b/1* DP1.4
2 x RS-232/422/485, 2 x RS-232
19V DC-in

DF35-ARK2-339946A1



ARM-based Board

102 x 146mm
Rockchip® ARM Cortex A72 + Cortex A53 Processor
Onboard LPDDR4 1866MHz 4GB
64GB Flash up to 64GB
1 x Realtek RTL8211E GbE
1 x Realtek RTL8152B-VB-CG 10/100Mbps
2 x Rear USB 3.0(Co-lay OTG),
6 x INT USB2.0
1 x HDMI, 1 x LVDS, 1 x eDP
2 x INT RS232, 2 x INT UART
12V DC-in

OTH-ARK3-356843A1



ARM-based Board

120 x 72mm
Rock Chip® ARM Cortex A55 RK3568
Onboard LPDD4X 3200MHz 4GB
32GB Flash up to 64GB
1 x Realtek RTL8211F GbE
2 x Rear USB 3.0(USB1 Co-lay OTG),
4 x INT USB 2.0
1 x HDMI, 1 x LVDS, 1 x eDP
2 x INT RS232, 3 x INT UART
12V DC-in


SMC-ARK1-358843A1



ARM-based Board

82 x 50mm
Rockchip® ARM Cortex A76 +
+A55 RK3588 Processor
Onboard LPDD4X 4266MHz 4GB
32GB Flash up to 128GB
1 x Realtek RTL8211F GbE
1 x Realtek RTL8111HS GbE

HBJC924R3288DG2NS



ARM-based Barebone

87(W) x 56(D) x 22.9(H) mm
Rockchip® ARM Cortex A17 RK3288
Processor
Onboard DDR3L 1333MHz 2GB,
8GB Flash up to 64GB
1 x Realtek GbE
4 x USB2.0
1 x HDMI, 1 x MIPI DSI, 1 x MIPI CSI
5V DC-in

HBJC923R3328T2NS



ARM-based Barebone

94.4 (W) x 60.5 (D) x 33.6 (H) mm
Rockchip® ARM Cortex A53 RK3328
Processor
Onboard DDR3L 1333MHz 2GB,
8GB Flash up to 32GB
1 x Realtek GbE
1 x USB3.0, 2 x USB2.0
1* x HDMI
5V DC-in

HPC070SC-FP6210



Projected Capacitive Type

205.0(W) x 144.0(H) x 54.5(D) mm

IP65, metal front bezel

7" With LED Backlight

1024 x 600, 320nits

1 x RS-232 (DB9 type),

1 x RS-232/422/485 (RJ45 type),

2 x USB3.2 (Gen1), 2 x 2.5GbE

1 x HDMI2.0b, 1 x 12~24V DC-in

Lock Jack, 1 x Power Button +

Power LED

12~24V DC-in

HPC101SC-FP6412



Projected Capacitive Type

268.49(W)x186.50(H)x59.70(D) mm

IP65, NEMA 4 rugged protection,
metal front bezel

10.1" With LED Backlight

1280 x 800, 400nits

2 x USB3.2 (Gen1), 2 x USB2.0,

1 x 8bit GPIO, 2 x RS232/422/485,

1 x HDMI2.0, 2 x 2.5GbE,

1 x 12~28V DC-in Lock Jack,

1 x Power button

12V DC-in

HPC185SC-FP6412



Projected Capacitive Type

464.80(W)x285.40(H)x73.50(D) mm

IP65, NEMA 4 rugged protection,
metal front bezel

10.1" With LED Backlight

1920 x 1080, 350nits

2 x USB3.2 (Gen1), 4 x USB2.0,

1 x 8bit GPIO, 2 x RS232/422/485,

2 x RS232, 1 x HDMI2.0, 2 x 2.5GbE,

1 x 12~28V DC-in Lock Jack,

1 x Power button

12~28V DC-in

HPC215SC-FP6412



Projected Capacitive Type

535.80(W)x303.31(H)x83.50(D) mm

IP65, NEMA 4 rugged protection,
full planar metal border

21.5" With LED Backlight

1920 x 1080, 250nits

2 x USB3.2 (Gen1), 4 x USB2.0,

1 x 8bit GPIO, 2 x RS232/422/485,

2 x RS232, 1* HDMI2.0, 2 x 2.5GbE,

1 x 12~28V DC-in Lock Jack,

1 x Power button

12V DC-in

HPC150GR-HD6412



5 Wires Analog Resistive Type

366.0(W) x 290.0(H) x 74.0(D) mm

IP65, NEMA 4 rugged protection,
metal front bezel

15" With LED Backlight

102 x 768, 350nits

2 x USB3.0, 2 x RS232/422/485,

4 x USB2.0, 2 x RS232, 1 x VGA,

1 x 8bit GPIO, 2 x GbE

1 x 9~28V DC-in Lock Jack,

1 x Power button

9~28V DC-in

HPC156C-DCP1135G7



Projected Capacitive Type

406.81(W)x259.12(H)x56.00(D)mm

IP65, NEMA 4 rugged protection,
metal front bezel

15.6" With LED Backlight

1920 x 1080, 250nits

2 x USB3.2 (Gen2), 4 x USB2.0,

2 x RS232/422/485, 2 x RS232/GPIO,

1 x HDMI, 1 x AT/ATX Mode Button,

1 x GbE, 1 x 2.5GbE, 1 x 12~36V

DC-in Lock Jack, 2 x Power button

12~36V DC-in

HPC215C-DCP6305E



Projected Capacitive Type

535.80(W)x327.31(H)x68.50(D) mm

IP65, NEMA 4 rugged protection,
metal front bezel

21.5" With LED Backlight

1920 x 1080, 250nits

2 x USB3.2 (Gen2), 4 x USB2.0,

2 x RS232/422/485, 2 x RS232/GPIO,

1 x HDMI, 1 x AT/ATX Mode Button,

1 x 2.5GbE, 1 x GbE, 1 x 12~36V DC-in

Lock Jack, 2 x Power button

12~36V DC-in

HPC270C-DCP1135G7



LG in-cell Touch

611.20(W)x359.18(H)x59.00(D) mm

IP65 front bezel

27" With LED Backlight

1920 x 1080, 300nits

2 x USB3.2 (Gen2), 4 x USB2.0,

2 x RS232/422/485, 2 x RS232/GPIO,

1 x HDMI, 1 x AT/ATX Mode Button,

1 x 2.5GbE, 1 x GbE, 1 x 12~36V

DC-in Lock Jack, 2 x Power button

12V DC-in

HPC-101 Series



HPC-133 Series



Projected Capacitive Type

259.3(W) x 177.3(H) x 39.0(D) mm

IP65, NEMA 4 rugged protection,
metal front bezel

10.1" With LED Backlight

1280 x 800, 350nits

2 x USB2.0 (USB1 Co-lay OTG),

1 x HDMI1.4, 1 x Audio, 1 x Micro SD

Socket, 1 x Power button, 1 x GbE,

1 x 12V DC-in, 1 x 44V~57V PoE PD

(HPC-P101)

12V DC-in / 44~57V input

Projected Capacitive Type

259.3(W) x 177.3(H) x 39.0(D) mm

IP65, NEMA 4 rugged protection,
metal front bezel

13.3" With LED Backlight

1920 x 1080, 300nits

2 x USB2.0 (USB1 Co-lay OTG),

1 x HDMI1.4, 1 x Audio, 1 x Micro SD

Socket, 1 x Power button, 1 x GbE,

1 x 12V DC-in, 1 x 44V~57V PoE PD

(HPC-P133)

12V DC-in / 44~57V input